



GENERAL INFORMATION

The elektraLite **Burst Strobe** is a strongly powerful LED strobe designed for both intensity and digital effects.

With 336 half-watt LED's, the elektraLite **Burst Strobe** is a powerful fixture. Designed with cool 7,200K diodes, this strobe light has a wide 120 degree beam angle, allowing for wide coverage with less fixtures. The half-watt diode allows for quicker cooling and more impact, as well as effects.

The elektraLite **Burst Strobe** has built-in features, including eight rings of LED diodes for hypnotic effects. Pulse, random, and scatter settings allow for a wide variety of strobe, lightning and electrical effects. Additionally, individual control of each of the eight rings, allows for shape effects as well as hypnotic and intensity rush effects.

A powerful, well-rounded LED effects fixture with a rugged design, the elektraLite **Burst Strobe** is a double-duty workhorse, ready to bring rich, bright white light to a wide variety of public spaces including stages, classrooms, galleries, worship spaces, studios, event spaces, live event, and production environments.

A user-friendly onboard control interface allows for multiple control options including master/slave, DMX, simple-strobe, and console-free static operation. The elektraLite **Burst Strobe** has 5-pin XLR DMX connectors (both in and thru). With a convenient, strong double-yoke included standard, mounting options are limitless.

FEATURES

- 336 half-watt cool white (7,200K) LED's for diversity of coverage, built-in effects options, and maximum cooling desirability
- built-in and configurable effects, including PULSE, RANDOM, SCATTER, HYPNOTIC, and RING CHASE
- clean, flicker-free on camera operation
- strong double yoke allows for floor mount or hanging
- variable adjustable speed strobe effect
- wide-angle 120 degree beam spread for maximum coverage capabilities
- can be run in stand-alone or master/slave configuration, with or without a control source, for fast, effective, and efficient operation
- double-slot gel frame holder and accessory slot with clip built-in

ORDERING INFORMATION

ELE772

Burst LED Strobe



ELE772

Burst Strobe

(336) 0.5W Cool White (7,200K) LED Strobe

SPECIFICATIONS

- Power Consumption - 180 watts (1.9A)
- Electrical - multi-voltage; AC 100-240V – 50/60Hz
- Housing - black aluminum
- Materials - corrosion resistant hardware
- Yoke - rigid flat steel
- Light Engine - (336) 0.5-watt LED emitters
- Control - DMX-512A (in and thru) via 5-pin XLR
- Ratings / Certifications - ETL listing to UL1573

ACCESSORIES

Accessories Included with each **Burst Strobe** are as follows:

- (1) double-yoke
- (1) 24" integrated power cable with Edison connector

DMX PROFILE

Depending on personality chosen, the **Burst Strobe** requires 12 channels of DMX. Consult the User Manual for further details.

CH	ACTION DESCRIPTION	VALUE
1	Grand Master for Strobe	0-255
2	Circle 1 Dimmer (innermost ring)	0-255
3	Circle 2 Dimmer	0-255
4	Circle 3 Dimmer	0-255
5	Circle 4 Dimmer	0-255
6	Circle 5 Dimmer	0-255
7	Circle 6 Dimmer	0-255
8	Circle 7 Dimmer (outer ring)	0-255
9	Strobe Effects*	0-255
10	Built-In Programs*	16-255
11	Built-In Programs Speed Control	2-255
12	Dimmer Curve	0-255

* = consult manual for full DMX Profile details

*THIS AREA
INTENTIONALLY
LEFT BLANK.*

DIMENSIONS CHART

Physical Dimensions			Shipping Dimensions		
Height	Length	Width	Height	Length	Width
9"	11"	89"	14"	14"	11"

WEIGHTS CHART

Weight		Shipping Weight	
lbs	kgs	lbs	kgs
9.7	4.4	11.5	5.2

