



Accessories Sold Separately

## GENERAL INFORMATION

The **elektraLite Stingray Mini** brings clean, warm white light in an incomparable level of intensity for its range.

At the heart of the **Stingray Mini** is a newly designed 20 watt COB LED. With a balanced 3,200K color temperature, the ellipsoidal WW provides the same clean, rich, beautiful white light audiences have grown accustomed to, making the **Stingray Mini** perfect for any show or event. The built-in accessory clip and included color frame allow for diffusion and color media to be used.

The **Stingray Mini's** sophisticated, proprietary diffraction lensing system provides a packed punch of light in a variety of beam spreads. The interchangeable lens tube give the user 26°, 36°, or 50° beam spreads. Four independent shutter blades give perfect in-focus cuts to the beam.

A powerful, well-rounded LED lighting fixture with a rugged all-metal design, the **Stingray Mini** is a perfect feature fixture, ready to bring rich, bright white light to a wide variety of public spaces including stages, classrooms, galleries, worship spaces, studios, event spaces, live event, and production environments.

A quick rotating and release of the barrel allows lens and shutter to be easily cleaned. Housing features rotating barrel assembly, pattern holder slot, and four shutter blades for perfect in-focus beam cuts.

## FEATURES

- single COB 20 watt LED giving rich consistent warm white at a balanced 3,200K color temperature for true theatrical white light with no hot spot
- 0-100% dimming using DMX version
- 19 degree lens installed. Available 26, 36 and 50 lens tubes with no chromatic aberration.
- double slot gel frame holder with safety clip for accessories and gel frame
- housing features rotating barrel assembly, pattern holder slot, and four shutter blades for perfect in-focus beam cuts
- DMX driver is remote-mountable, up to 10' from fixture

## ORDERING INFORMATION

ELE823-MINI	Stingray Profile mini w/ 19° lens
ELE823-MINIDMX	Stingray Profile mini DMX w/ 19° lens
ELE823-MINI-GEL	Stingray Profile mini Gel Frame
ELE823-MINI-GH	Stingray Profile mini Gobo Holder
ELE823-TRACK	Eurotrack Adapter
ELE823-MINI-LENS**	Stingray Profile mini Lens (specify 26°, 36°, or 50°)



# ELE823-MINI

# Stingray mini

(1) 20W 3,200K Warm White LED Mini Spot

## SPECIFICATIONS

- Power Consumption - 25 watts (0.3A)  
- maximum five fixtures per 30A circuit
- Electrical - multi-voltage; AC 100-250V – 50/60Hz
- Housing - aluminum monocoque design
- Materials - corrosion resistant hardware
- Yoke - rigid flat steel
- Light Engine - single 20W COB LED emitter
- Refresh Rate - variable
- Optics / Lensing(s) - Variable PC lensing

## ACCESSORIES

Accessories Included with each **Stingray Mini** are as follows:

- (1) single yoke
- (1) adjustable 19 degree lens tube
- (1) Wireless Remote Control

## DIMENSIONS CHART

Physical Dimensions			Shipping Dimensions		
Length	Width	Height	Length	Width	Height
11.3"	4.3"	4.0"	13.8"	6.5"	6.0"

## WEIGHTS CHART

Weight		Shipping Weight	
lbs	kgs	lbs	Kgs
4.0	1.9	5.0	2.3

**This space intentionally left blank.**

