

## Burst Strobe

ELE772 (336) 0.5W Cool White (7,200K) LED Strobe



### GENERAL INFORMATION

The elektraLite **Burst Strobe** is a strongly powerful LED strobe designed for both intensity and digital effects.

With 336 half-watt LED's, the elektraLite **Burst Strobe** is a powerful fixture. Designed with cool 7,200K diodes, this strobe light has a wide 120 degree beam angle, allowing for wide coverage with less fixtures. The half-watt diode allows for quicker cooling and more impact, as well as effects.

The elektraLite **Burst Strobe** has built-in features, including eight rings of LED diodes for hypnotic effects. Pulse, random, and scatter settings allow for a wide variety of strobe, lightning and electrical effects. Additionally, individual control of each of the eight rings, allows for shape effects as well as hypnotic and intensity rush effects.

A powerful, well-rounded LED effects fixture with a rugged design, the elektraLite **Burst Strobe** is a double-duty workhorse, ready to bring rich, bright white light to a wide variety of public spaces including stages, classrooms, galleries, worship spaces, studios, event spaces, live event, and production environments.

A user-friendly onboard control interface allows for multiple control options including master/slave, DMX, simple-strobe, and console-free static operation. The elektraLite **Burst Strobe** has 5-pin XLR DMX connectors (both in and thru). With a convenient, strong double-yoke included standard, mounting options are limitless.

### FEATURES

- 336 half-watt cool white (7,200K) LED's for diversity of coverage, built-in effects options, and maximum cooling desirability
- built-in and configurable effects, including PULSE, RANDOM, SCATTER, HYPNOTIC, and RING CHASE
- clean, flicker-free on camera operation
- strong double yoke allows for floor mount or hanging
- variable adjustable speed strobe effect
- wide-angle 120 degree beam spread for maximum coverage capabilities
- can be run in stand-alone or master/slave configuration, with or without a control source, for fast, effective, and efficient operation
- double-slot gel frame holder and accessory slot with clip built-in

### ORDERING INFORMATION

ELE772

Burst LED Strobe

# Burst Strobe

**ELE772** (336) 0.5W Cool White (7,200K) LED Strobe

## SPECIFICATIONS

Power Consumption	- 180 watts (1.9A)
Electrical	- multi-voltage; AC 100-240V – 50/60Hz
Housing	- black aluminum
Materials	- corrosion resistant hardware
Yoke	- rigid flat steel
Light Engine	- (336) 0.5-watt LED emitters
Control	- DMX-512A (in and thru) via 5-pin XLR
Ratings / Certifications	- ETL listing to UL1573

## ACCESSORIES

Accessories Included with each **Burst Strobe** are as follows:

- (1) double-yoke
- (1) 24" integrated power cable with Edison connector

## DMX PROFILE

Depending on personality chosen, the **Burst Strobe** requires 12 channels of DMX. Consult the User Manual for further details.

CH	ACTION DESCRIPTION	VALUE
1	Grand Master for Strobe	0-255
2	Circle 1 Dimmer (innermost ring)	0-255
3	Circle 2 Dimmer	0-255
4	Circle 3 Dimmer	0-255
5	Circle 4 Dimmer	0-255
6	Circle 5 Dimmer	0-255
7	Circle 6 Dimmer	0-255
8	Circle 7 Dimmer (outer ring)	0-255
9	Strobe Effects*	0-255
10	Built-In Programs*	16-255
11	Built-In Programs Speed Control	2-255
12	Dimmer Curve	0-255

\* = consult manual for full DMX Profile details

*THIS AREA  
INTENTIONALLY  
LEFT BLANK.*

## DIMENSIONS CHART

Physical Dimensions			Shipping Dimensions		
Height	Length	Width	Height	Length	Width
9"	11"	89"	14"	14"	11"

## WEIGHTS CHART

Weight		Shipping Weight	
lbs	kgs	lbs	kgs
9.7	4.4	11.5	5.2

