



GENERAL INFORMATION

The **elektraLite Stingray Mini** brings a choice of Warm White, Cool White, and Variable White in an incomparable level of intensity for its range.

At the heart of the **Stingray Mini** is a newly designed 20 watt COB LED. The ellipsoidal provides clean, rich, beautiful white light making the Stingray Mini perfect for any show or event. The built-in accessory clip allows for diffusion and color media to be used.

The **Stingray Mini's** sophisticated, proprietary diffraction lensing system provides a packed punch of light in a variety of beam spreads. The interchangeable lens tube give the user 19°, 26°, 36°, or 50° beam spreads. Four independent shutter blades give perfect in-focus cuts to the beam.

A powerful, well-rounded LED lighting fixture with a rugged all-metal design, the **Stingray Mini** is a perfect feature fixture, ready to bring rich, bright white light to a wide variety of public spaces including stages, classrooms, galleries, worship spaces, studios, event spaces, live event, and production environments.

A quick rotating and release of the barrel allows lens and shutter to be easily cleaned. Housing features rotating barrel assembly, pattern holder slot, and four shutter blades for perfect in-focus beam cuts.

FEATURES

- single COB 20 watt LED giving rich consistent white light with no hot spot
- 0-100% dimming using DMX version
- Available in 19°, 26°, 36° and 50° lens tubes with no chromatic aberration.
- double slot gel frame holder with safety clip for accessories and gel frame
- housing features rotating barrel assembly, pattern holder slot, and four shutter blades for perfect in-focus beam cuts

ORDERING INFORMATION

| | |
|------------------|---------------------------------------|
| SRAYM WW DMX 19D | Stingray Profile Mini DMX w/ 19° lens |
| SRAYM WW DMX 26D | Stingray Profile Mini DMX w/ 26° lens |
| SRAYM WW DMX 36D | Stingray Profile Mini DMX w/ 36° lens |
| SRAYM WW DMX 50D | Stingray Profile Mini DMX w/ 50° lens |

| | |
|------------------|---------------------------------------|
| SRAYM CW DMX 19D | Stingray Profile Mini DMX w/ 19° lens |
| SRAYM CW DMX 26D | Stingray Profile Mini DMX w/ 26° lens |
| SRAYM CW DMX 36D | Stingray Profile Mini DMX w/ 36° lens |
| SRAYM CW DMX 50D | Stingray Profile Mini DMX w/ 50° lens |

| | |
|------------------|---------------------------------------|
| SRAYM VW DMX 19D | Stingray Profile Mini DMX w/ 19° lens |
| SRAYM VW DMX 26D | Stingray Profile Mini DMX w/ 26° lens |
| SRAYM VW DMX 36D | Stingray Profile Mini DMX w/ 36° lens |
| SRAYM VW DMX 50D | Stingray Profile Mini DMX w/ 50° lens |

| | |
|-----------------|-----------------------------------|
| ELE823-MINI-GEL | Stingray Profile mini Gel Frame |
| ELE823-MINI-GH | Stingray Profile mini Gobo Holder |
| ELE823-TRACK | Eurotrack Adapter |

Stingray Mini DMX

(1) 20W 3,200K Warm White LED Mini Spot

SPECIFICATIONS

| | |
|---------------------|--|
| Power Consumption | - 25 watts (0.3A) - maximum five fixtures per 30A circuit |
| Electrical | - multi-voltage; AC 100-250V – 50/60Hz |
| Housing | - aluminum monocoque design |
| Materials | - corrosion resistant hardware |
| Yoke | - rigid flat steel |
| Light Engine | - single 20W COB LED emitter |
| Refresh Rate | - variable |
| Optics / Lensing(s) | - Variable PC lensing |

ACCESSORIES

Accessories Included with each **Stingray Mini** are as follows:

- (1) single yoke
- (1) adjustable lens tube
- (1) Wireless Remote Control

DIMENSIONS CHART

| Physical Dimensions | | | Shipping Dimensions | | |
|---------------------|-------|--------|---------------------|-------|--------|
| Length | Width | Height | Length | Width | Height |
| 11.3" | 4.3" | 4.0" | 13.8" | 6.5" | 6.0" |

WEIGHTS CHART

| Weight | | Shipping Weight | |
|--------|-----|-----------------|-----|
| lbs | kgs | lbs | Kgs |
| 4.0 | 1.9 | 5.0 | 2.3 |

This space intentionally left blank.