



Accessories Sold Separately

GENERAL INFORMATION

The **elektraLite Stingray Mini** brings a choice of Warm White, Cool White, and Variable White in an incomparable level of intensity for its range.

At the heart of the **Stingray Mini** is a newly designed 20 watt COB LED. The ellipsoidal provides clean, rich, beautiful white light making the Stingray Mini perfect for any show or event. The built-in accessory clip allows for diffusion and color media to be used.

The **Stingray Mini's** sophisticated, proprietary diffraction lensing system provides a packed punch of light in a variety of beam spreads. The interchangeable lens tube give the user 19°, 26°, 36°, or 50° beam spreads. Four independent shutter blades give perfect in-focus cuts to the beam.

A powerful, well-rounded LED lighting fixture with a rugged all-metal design, the **Stingray Mini** is a perfect feature fixture, ready to bring rich, bright white light to a wide variety of public spaces including stages, classrooms, galleries, worship spaces, studios, event spaces, live event, and production environments.

A quick rotating and release of the barrel allows lens and shutter to be easily cleaned. Housing features rotating barrel assembly, pattern holder slot, and four shutter blades for perfect in-focus beam cuts.

FEATURES

- single COB 20 watt LED giving rich consistent white light with no hot spot
- 0-100% dimming using DMX version
- Available in 19°, 26°, 36° and 50° lens tubes with no chromatic aberration.
- double slot gel frame holder with safety clip for accessories and gel frame
- housing features rotating barrel assembly, pattern holder slot, and four shutter blades for perfect in-focus beam cuts

ORDERING INFORMATION

SRAYM WW DMX 19D	Stingray Profile Mini DMX w/ 19° lens
SRAYM WW DMX 26D	Stingray Profile Mini DMX w/ 26° lens
SRAYM WW DMX 36D	Stingray Profile Mini DMX w/ 36° lens
SRAYM WW DMX 50D	Stingray Profile Mini DMX w/ 50° lens

SRAYM CW DMX 19D	Stingray Profile Mini DMX w/ 19° lens
SRAYM CW DMX 26D	Stingray Profile Mini DMX w/ 26° lens
SRAYM CW DMX 36D	Stingray Profile Mini DMX w/ 36° lens
SRAYM CW DMX 50D	Stingray Profile Mini DMX w/ 50° lens

SRAYM VW DMX 19D	Stingray Profile Mini DMX w/ 19° lens
SRAYM VW DMX 26D	Stingray Profile Mini DMX w/ 26° lens
SRAYM VW DMX 36D	Stingray Profile Mini DMX w/ 36° lens
SRAYM VW DMX 50D	Stingray Profile Mini DMX w/ 50° lens

SRAYM GEL FRM	Stingray Profile mini Gel Frame
SRAYM GOBO HLDR	Stingray Profile mini Gobo Holder
ELE823-TRACK	Eurotrack Adapter

Stingray Mini DMX

(1) 20W 3,200K Warm White LED Mini Spot

SPECIFICATIONS

Power Consumption	- 25 watts (0.3A) - maximum five fixtures per 30A circuit
Electrical	- multi-voltage; AC 100-240V – 50/60Hz
Housing	- aluminum monocoque design
Materials	- corrosion resistant hardware
Yoke	- rigid flat steel
Light Engine	- single 20W COB LED emitter
Refresh Rate	- variable
Optics / Lensing(s)	- Variable PC lensing

ACCESSORIES

Accessories Included with each Stingray Mini are as follows:

- (1) single yoke
- (1) adjustable lens tube
- (1) Wireless Remote Control

DIMENSIONS CHART

Physical Dimensions			Shipping Dimensions		
Length	Width	Height	Length	Width	Height
11.3"	4.3"	4.0"	13.8"	6.5"	6.0"

WEIGHTS CHART

Weight		Shipping Weight	
lbs	kgs	lbs	Kgs
4.0	1.9	5.0	2.3

This space intentionally left blank.